



Date of issue : 05/01/2005

Last. mod. date : 11/05/2009

Product code**04236 RI-JET 100 REMOV/BLACKOUT GLOSS WHITE AVM removable BLACK WK 1****Description**

Gloss white soft vinyl, with a specific formulation and characteristics that make it proper to be used for Solvent Ink-Jet.

Solvent and eco-solvent ink-jet printing. The RI-JET series of ink jet print media give excellent print results with UV ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Semi-permanent acrylic adhesive with a good initial tack and with easy repositioning.

For indoor (like in POS) and outdoor posters, billboards and signs applications.

Technical data**FACE MATERIAL**

Type	Monomeric soft vinyl
Colour and Finish	Gloss white
Weight	140g/m ²
Thickness	100μ

ADHESIVE

Reference	AVM removable
Type	Acrylic semipermanent
Min. Appl. Temp.	+10°C
Service Temp.	-20°C/+80°C
Shear	High
Tack FTM9	>2N/inch ²
FinAdh FTM2	>2N/inch

RELEASE BACKING

Type	1 side clay coated
Colour and Finish	White
Weight	140g/m ²
Thickness	135μ

CHEMICAL RESISTANCE

Detergent	No effect (24Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.