



Date of issue : 05/01/2005

Last. mod. date : 11/05/2009

Product code**04062 RI-JET 50 CAST CLEAR ASP 26 permanent WKPE 144****Description**

Clear gloss CAST vinyl film.

Solvent and eco-solvent ink-jet printing. The RI-JET series of ink jet print media give excellent print results with UV ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Acrylic permanent solvent based adhesive.

Designed for extended outdoor durability these films are ideal for high-impact recreational vehicles, fleet graphics, architectural signage and computerized sign marking.

Technical data**FACE MATERIAL**

Type	Cast soft vinyl
Colour and Finish	Clear, gloss
Weight	70g/m ²
Thickness	50μ

ADHESIVE

Reference	RI - ASP26
Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-20°C/ +130°C
Shear	Very high
Tack	Medium
Ultimate Adhesion	High

RELEASE BACKING

Type	1 side silicone coated 2 side PE coated Kraft
Colour and Finish	White
Weight	144g/m ²
Thickness	166μ

CHEMICAL RESISTANCE

Detergent	No effect (24 Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% NH4OH	No effect (10 min)
10% HCl	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.