



Date of issue : 05/01/2005

Last. mod. date : 11/05/2009

Product code**05134 RI-JET DECOBUS ASP 30 semipermanent WK 140****Description**

Plasticised white vinyl film, semi-gloss, flexible and with good conformability.

Solvent and eco-solvent ink-jet printing. The RI-JET series of ink jet print media give excellent print results with UV ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Semi-permanent acrylic adhesive with a good initial tack and easy repositioning.

Specially designed for decorative advertising on buses. Its very good break resistance allows an easy removal even for big size signs.

Technical data**FACE MATERIAL**

Type	Plasticised vinyl film
Colour and Finish	White, semi-gloss
Weight	115g/m ²
Thickness	85μ

ADHESIVE

Reference	RI - ASP30
Type	Semi-permanent acrylic
Min. Appl. Temp.	+ 10°C
Service Temp.	-30°C/ +100°C
Shear	Good
Tack	Medium
Ultimate Adhesion	Medium

RELEASE BACKING

Type	1 side clay coated kraft paper
Colour and Finish	White
Weight	140g/m ²
Thickness	135μ

CHEMICAL RESISTANCE

Detergent	No effect (24Hrs)
Gasoline	No effect (1 Hrs)
SAE20 Motoroil	No effect (24 Hrs)
10% HCl	No effect (10 min)
10% NH4OH	No effect (10 min)

Storage

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.