



Date of issue : 05/01/2005

Last. mod. date : 11/05/2009

**Product code****04060 RI-JET TRANSLUCENT WHITE ASP 30 semipermanent WK 140****Description**

Translucent white polymeric soft vinyl.

Solvent and eco-solvent ink-jet printing. The RI-JET series of ink jet print media give excellent print results with UV ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

The semipermanent adhesive gives a good initial tack and easy repositioning.

Specifically developed for large format solvent based ink-jet and vehicles decoration. Particularly suitable for illuminated signs and window graphics.

**Technical data****FACE MATERIAL**

Type	Soft polymeric vinyl
Colour and Finish	Translucent, white
Weight	106g/m <sup>2</sup>
Thickness	90μ

**ADHESIVE**

Reference	ASP 30
Type	Acrylic removable
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+100°C
Shear	High
Tack FTM9	9N/inch <sup>2</sup>
FinAdh FTM2	5N/inch

**RELEASE BACKING**

Type	1 side clay coated
Colour and Finish	White
Weight	135g/m <sup>2</sup>
Thickness	140μ

**Storage**

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity. Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.

All values presented in pdf data sheet are typical. Ritrama's data sheets provide only the general characteristics of the Product. It is the responsibility of the Customer and/or End User to determine that the Product is fit for the purpose for which the Customer and/or End User wish to use it. Ritrama can give no guarantee beyond the information given in the data sheet.